



ISS UCR Entry



Small & Medium Market
Powerfull Server for Business
Communications

ISS UCR Business 450



Enterprise-Level
Communications Server For
Growing Business

ISS UCR Business 550



Enterprise-Level
Communications Server for Big
Business

TELEPHONY					
Concurrent Calls	Up to 60*		Up to 120*		Up to 600*
Extensions	Up to 110*		Up to 300*		Up to 1200*
Analog Ports	4/8/GSM		Up 48		Up 72
Digital Ports	Up to 1 E1/T1/J1 or up to 4 BRI		Up to 4 E1/T1/J1		Up to 8 E1/T1/J1
PCI Slots	1 PCIe**		2 PCIe - Easy Swap		5 (1 PCI, 4 PCIe)
Operative System	Issabel 4.0		Issabel 4.0		Issabel 4.0
HARDWARE					
CPU	2 Core Intel Celeron Dual Core N2807 1.58GHz		4 Core Intel Celeron N2807 1.6GHz		2.2GHz Quad Core
2nd CPU	-		PRO Version		2.2GHz Quad Core
Hard Disk Drive	16 GB mSATA SSD		1st Hard Drive : 500 GB HDD 2nd Hard Drive: 500 GB HDD (optional)		2x 500 GB - 3.5'' (SW RAID 1) Optional upgrade to Solid State Drives
RAID	-		Hardware RAID 1		SoftRAID 1
RAID Controller	-		✓		Optional
Memory (RAM)	2 GB DDR3L (Default) Up to 4GB DDR3L		2 GB DDR3L (Default) Up to 8GB DDR3L		4 GB DDR3L (Up to 8 GB)
Network Interfaces	3 Ethernet Channels (10/100/1000Mbps Speed)		2 Ethernet Channels (10/100/1000Mbps Speed)		2 Ethernet Channels (10/100/1000Mbps Speed)
USB Ports	2 in Back Panel		2 in Back Panel		4 in Back Panel
POWER SUPPLY					
Rated Power	14W		150 W, eficient PSU		500 W HS Redundant PSU
Operating Voltage	120/240v Auto Switching		100/240v Auto Switching		100/240v Auto Switching
Redudant Power Supply	-		PRO Version		✓
DIMENSIONS					
Height	2.20'' (56 mm)		2.64" (67 mm) - 1.5 Rack Units		3.50'' (89 mm) - 2 RacksUnits
Width	7.13'' (181 mm)		17.32" (440 mm)		17.20'' (437 mm)
Depth	6.42'' (163 mm)		14.65" (372 mm)		19.09'' (485 mm)
Weight	0.84 Kg (1.85 lb)		4.3 Kg (9.5 lb)		9 Kg (19.84 lb)

*: Represents a safe estimate on a basic scenario. Visit <http://elx.ec/benchmark> for more details.

***: Only a limited number of telephony cards models supported (chosen when ordering).